


Plug and Sockets

BCZ8060 Series Explosion-proof Plug and Sockets



- ◆ Explosion protection to
 - CENELEC
 - IEC
 - NEC
- ◆ Can be used in
 - Zone 1 and Zone 2
 - Zone 21 and Zone 22
 - Class I, Zone 1 and Zone 2
 - Class I, Division 2, Groups A, B, C, D
- ◆ 2P, 3P, 4P and 5P.
- ◆ Plug can only be pulled out when switch is off; turn on the power after inserting the plug.
- ◆ GRP (glass fibre-reinforced polyester resin).

Catalogue number logic



Zones 1&2; 21&22

Plug and Sockets

BCZ8060 Series Explosion-proof Plug and Sockets

Selection table

Version	Voltage (V)	Current (A)	Number of pole	Schematic diagram	h	Ordering code	Weight (kg)
BCZ8060-16/□/□ 	480~500	16	3P+PE		7	30048	1.85
	380~415	16	3P+N+PE		6	30049	1.85
		16	3P+PE		6	30050	1.85
	200~250	16	3P+N+PE		6	30051	1.85
		16	3P+PE		9	30052	1.85
		16	2P+PE		6	30053	1.85
	100~130	16	1P+N+PE		4	30054	1.85
	36	16	2P+PE		12	30055	1.80
		16	2P			30056	1.80
	24	16	2P+PE		12	30057	1.80
		16	2P			30058	1.80
BCZ8060-32/□/□ 	600~690	32	3P+PE		5	30059	2.85
	480~500	32	3P+PE		7	30060	2.85
	380~415	32	3P+N+PE		6	30061	2.85
		32	3P+PE		6	30062	2.85
	200~250	32	3P+N+PE		6	30063	2.85
		32	3P+PE		9	30064	2.85
BCZ8060-63/□/□ 	380~415	63	3P+N+PE	/	/	30065	14.90
		63	3P+PE	/	/	30066	14.90
	200~250	63	1P+N+PE	/	/	30067	14.90
BCZ8060-125/□/□ 	600~690	125	3P+PE		5	30068	16.00
	480~500	125	3P+PE		7	30069	16.00
	380~415	125	3P+N+PE		6	30070	16.00
		125	3P+PE		6	30071	16.00
	200~250	125	3P+N+PE		6	30072	16.00
		125	3P+PE		9	30073	16.00

Plug and Sockets

BCZ8060 Series Explosion-proof Plug and Sockets

Technical data

Explosion-proof plug and sockets BCZ8060-16/□/□

Explosion protection

Gas explosion protection

II 2 G Ex d e IIC T6 Gb

Dust explosion protection

II 2 D Ex tb IIIC T80°C Db IP65

Certificates

EUT 14 ATEX 1153; IECEX CQM 13.0043X

Conformity to standards

EN 60079-0:2012, EN 60079-1:2007, EN 60079-7:2007, EN 60079-31:2009
IEC 60079-0:2011, IEC 60079-1:2007, IEC 60079-7:2006, IEC 60079-31:2008

Enclosure material

GRP (glass fibre-reinforced polyester resin)

Exposed fastener

Stainless steel

Rated voltage

AC 480V~500V, 380V~415V, 200V~250V, 100V~130V

DC 36V, 24V

Rated current

16A

Degree of protection

IP65

Ambient temperature

-20°C~+55°C

Cable entries

Standard 1 x G3/4" cable gland(plastic), 1 x G3/4" plug (plastic)

Cable gland (optional)

DQM-I (Ex e) is recommended. Please see P7/16.

Cross section of cable

2.5~4 mm²

Accessories and spare parts

Version	Voltage (V)	Current (A)	Number of pole	Schematic diagram	h	Colour	Ordering Code	Weight (kg)
16A Coupler	480 ~ 500	16	3P+PE		7	Black	30099	1.30
	380 ~ 415	16	3P+N+PE		6	Red	30100	1.30
		16	3P+PE		6	Red	30101	1.30
	200 ~ 250	16	3P+N+PE		6	Blue	30102	1.30
		16	3P+PE		9	Blue	30103	1.30
		16	2P+PE		6	Blue	30104	1.30
	100 ~ 130	16	1P+N+PE		4	Yellow	30105	1.30
	36	16	2P+PE		12	Violet	30106	1.25
		16	2P			Violet	30107	1.25
	24	16	2P+PE		12	Violet	30108	1.25
		16	2P			Violet	30109	1.25



Plug and Sockets

BCZ8060 Series Explosion-proof Plug and Sockets

Accessories and spare parts

Version	Voltage (V)	Current (A)	Number of pole	Schematic diagram	h	Colour	Ordering Code	Weight (kg)
 16A Socket	480 ~ 500	16	3P+PE		7	Black	30075	1.50
	380 ~ 415	16	3P+N+PE		6	Red	30076	1.50
		16	3P+PE		6	Red	30077	1.50
	200 ~ 250	16	3P+N+PE		6	Blue	30078	1.50
		16	3P+PE		9	Blue	30079	1.50
		16	2P+PE		6	Blue	30080	1.50
	100 ~ 130	16	1P+N+PE		4	Yellow	30081	1.50
	36	16	2P+PE		12	Violet	30082	1.45
		16	2P			Violet	30083	1.45
	24	16	2P+PE		12	Violet	30084	1.45
		16	2P			Violet	30085	1.45
 16A Plug	480 ~ 500	16	3P+PE		7	Black	30087	0.35
	380 ~ 415	16	3P+N+PE		6	Red	30088	0.35
		16	3P+PE		6	Red	30089	0.35
	200 ~ 250	16	3P+N+PE		6	Blue	30090	0.35
		16	3P+PE		9	Blue	30091	0.35
		16	2P+PE		6	Blue	30092	0.35
	100 ~ 130	16	1P+N+PE		4	Yellow	30093	0.35
	36	16	2P+PE		12	Violet	30094	0.35
		16	2P			Violet	30095	0.35
	24	16	2P+PE		12	Violet	30096	0.35
		16	2P			Violet	30097	0.35

Plug and Sockets

BCZ8060 Series Explosion-proof Plug and Sockets

Technical data

Explosion-proof plug and sockets BCZ8060-32/□/□

Explosion protection

Gas explosion protection

Dust explosion protection

Certificates

Conformity to standards

Enclosure material

Exposed fastener

Rated voltage

Rated current

Degree of protection

Ambient temperature

Cable entries

Cable gland (optional)

Cross section of cable

Ex II 2 G Ex d e IIC T5 or T4 Gb

Ex II 2 D Ex tb IIIC T80°C Db IP65

EUT 14 ATEX 1153; IECEx CQM 13.0043X

EN 60079-0:2012, EN 60079-1:2007, EN 60079-7:2007, EN 60079-31:2009

IEC 60079-0:2011, IEC 60079-1:2007, IEC 60079-7:2006, IEC 60079-31:2008

GRP (glass fibre-reinforced polyester resin)

Stainless steel

AC 600V~690V, 480V~500V, 380V~415V, 200V~250V

32A

IP65

T5 for Tamb: -20°C~+40°C, T4/T80°C for Tamb: -20°C~+55°C

Standard 1 x M40 x 1.5 cable gland (plastic), 1 x M40 x 1.5 plug(plastic)

DQM-I (Ex e) is recommended. Please see P7/16.

4~6 mm²

Accessories and spare parts

Version	Voltage (V)	Current (A)	Number of pole	Schematic diagram	h	Colour	Ordering Code	Weight (kg)
32A Socket 	600 ~ 690	32	3P+PE		5	Black	30110	1.90
	480 ~ 500	32	3P+PE		7	Black	30111	1.90
	380 ~ 415	32	3P+N+PE		6	Red	30112	1.90
		32	3P+PE		6	Red	30113	1.90
	200 ~ 250	32	3P+N+PE		6	Blue	30114	1.90
		32	3P+PE		9	Blue	30115	1.90
32A Plug 	600 ~ 690	32	3P+PE		5	Black	30116	0.95
	480 ~ 500	32	3P+PE		7	Black	30117	0.95
	380 ~ 415	32	3P+N+PE		6	Red	30118	0.95
		32	3P+PE		6	Red	30119	0.95
	200 ~ 250	32	3P+N+PE		6	Blue	30120	0.95
		32	3P+PE		9	Blue	30121	0.95
32A Coupler 	600 ~ 690	32	3P+PE		5	Black	30122	1.75
	480 ~ 500	32	3P+PE		7	Black	30123	1.75
	380 ~ 415	32	3P+N+PE		6	Red	30124	1.75
		32	3P+PE		6	Red	30125	1.75
	200 ~ 250	32	3P+N+PE		6	Blue	30126	1.75
		32	3P+PE		9	Blue	30127	1.75

Plug and Sockets

BCZ8060 Series Explosion-proof Plug and Sockets

Technical data

Explosion-proof plug and sockets BCZ8060-63/□/□

Explosion protection

Gas explosion protection

Ex II 2 G Ex d e IIC T5 or T4 Gb

Dust explosion protection

Ex II 2 D Ex tb IIIC T95°C Db IP65

Certificates

EUT 14 ATEX 1153; IECEx CQM 13.0041X

Conformity to standards

EN 60079-0:2012, EN 60079-1:2007, EN 60079-7:2007, EN 60079-31:2009
IEC 60079-0:2011, IEC 60079-1:2007, IEC 60079-7:2006, IEC 60079-31:2008

Enclosure material

GRP (glass fibre-reinforced polyester resin)

Exposed fastener

Stainless steel

Rated voltage

AC 380V~415V, 200V~250V

Rated current

63A

Degree of protection

IP65

Ambient temperature

T5 for Tamb: -20°C~+40°C, T4/T95°C for Tamb: -20°C~+55°C

Cable entries

Standard 1 x G1 1/2" cable gland (plastic)

Cable gland (optional)

DQM-I (Ex e) is recommended. Please see P7/16.

Cross section of cable

10~16 mm²

Accessories and spare parts

Version	Voltage (V)	Current (A)	Number of pole	Schematic diagram	Colour	Ordering Code	Weight (kg)
63A Socket 	380 ~ 415	63	3P+N+PE	/	Red	30128	12.75
		63	3P+PE		Red	30129	12.75
	200 ~ 250	63	1P+N+PE	/	Blue	30130	12.75
63A Plug 	380 ~ 415	63	3P+N+PE	/	Red	30131	2.15
		63	3P+PE	/	Red	30132	2.15
	200 ~ 250	63	1P+N+PE	/	Blue	30133	2.15



Plug and Sockets

BCZ8060 Series Explosion-proof Plug and Sockets

Technical data

Explosion-proof plug and sockets BCZ8060-125/□/□

Explosion protection

Gas explosion protection

Ex II 2 G Ex d e IIC T4 Gb

Dust explosion protection

Ex II 2 D Ex tb IIIC T95°C Db IP65

Certificates

EUT 14 ATEX 1153; IECEX CQM 13.0042X

Conformity to standards

EN 60079-0:2012, EN 60079-1:2007, EN 60079-7:2007, EN 60079-31:2009
IEC 60079-0:2011, IEC 60079-1:2007, IEC 60079-7:2006, IEC 60079-31:2008

Enclosure material

GRP (glass fibre-reinforced polyester resin)

Exposed fastener

Stainless steel

Rated voltage

AC 600V~690V, 480V~500V, 380V~415V, 200V~250V

Rated current

125A

Degree of protection

IP65

Ambient temperature

-20°C~+55°C

Cable entries

Standard 1 x G1 1/2" cable gland (plastic)

Cable gland (optional)

DQM-I (Ex e) is recommended. Please see P7/16.

Cross section of cable

25~35 mm²


Accessories and spare parts

Version	Voltage (V)	Current (A)	Number of pole	Schematic diagram	h	Colour	Ordering Code	Weight (kg)
	600 ~ 690	125	3P+PE		5	Black	30134	14.30
	480 ~ 500	125	3P+PE		7	Black	30135	14.30
	380 ~ 415	125	3P+N+PE		6	Red	30136	14.30
		125	3P+PE		6	Red	30137	14.30
	200 ~ 250	125	3P+N+PE		6	Blue	30138	14.30
		125	3P+PE		9	Blue	30139	14.30
	600 ~ 690	125	3P+PE		5	Black	30140	1.70
	480 ~ 500	125	3P+PE		7	Black	30141	1.70
	380 ~ 415	125	3P+N+PE		6	Red	30142	1.70
		125	3P+PE		6	Red	30143	1.70
	200 ~ 250	125	3P+N+PE		6	Blue	30144	1.70
		125	3P+PE		9	Blue	30145	1.70


Plug and Sockets

BCZ8060 Series Explosion-proof Plug and Sockets


Dimension drawings (all dimensions in mm) - subject to alteration





Plug and socket



Coupler (L)



Socket (Z)




Plug (T)


BCZ8060-16/□/□

BCZ8060-32/□/□


Version	L	H	L1	L2	H1	D	A	B	L3	D1
BCZ8060-16/□/(2P/3P)	336	154	356	227	120	90	80	122	171	72
BCZ8060-16/□/(4P/5P)	408	175	460	252	151	110	102	150	217	76.5
BCZ8060-32/□/□	460	209	514	283	171	120	113	169	253	95




Plug and socket




BCZ8060-63/□/□





Plug (T)



Plug and socket



Socket (Z)



Plug (T)

BCZ8060-125/□/□