



CO.SI.ME.
EQUIPMENT FOR ATEX

INTERRUTTORI DI PROTEZIONE
PROTECTION CIRCUIT BREAKER

EJB



GAS

II2G Ex d IIB+H₂ T6 ÷ T5

***IP65/IP66**

Zone 1 - Zone 21 - Zone 2 - Zone 22

DUST

II2D Ex tD A21 T80°C ÷ T95°C

***IP65/IP66**

❄ -20°C ÷ ☀ +40°C

❄ -20°C ÷ ☀ +60°C



Codice Code	Corrente Current [A]	Potenza Rated power kW @ 230V	Potenza Rated power kW @ 400V
EJB 544CM01	0,10 ÷ 0,16	-	-
EJB 544CM02	0,16 ÷ 0,25	-	0,06
EJB 544CM03	0,25 ÷ 0,4	0,06	0,09
EJB 544CM04	0,40 ÷ 0,63	-	0,12
EJB 544CM05	0,63 ÷ 1,0	-	0,25
EJB 544CM06	1,0 ÷ 1,6	0,25	0,37
EJB 544CM07	1,6 ÷ 2,5	0,37	0,75
EJB 544CM08	2,5 ÷ 4,0	0,75	1,10

Codice Code	Corrente Current [A]	Potenza Rated power kW @ 230V	Potenza Rated power kW @ 400V
EJB 544CM10	4,0 ÷ 6,3	1,10	2,20
EJB 544CM14	6,0 ÷ 10	2,20	3,00
EJB 544CM16	9,0 ÷ 14	3,00	5,50
EJB 544CM20	13 ÷ 18	4,00	7,50
EJB 544CM21	17 ÷ 23	5,50	9,00
EJB 544CM22	20 ÷ 25	6,00	11,0
EJB 544CM32	24 ÷ 32	7,50	15,0