

EMT is a steel raceway of circular cross section which is unthreaded.

The exterior is galvanized and protected by a clear zinc coating.

The interior is a smooth continuous raceway and is coated with zinc organic lubricants. It is installed either indoors or outdoors in all conditions and produced trade size from ½" to 4".

## EMT Pipes are manufactured in accordance with the latest edition of the following:

- American National Standard for Steel Electrical Metallic Tubing (ANSI C80.3)
- Underwriters Laboratories Standard for Electrical Metallic Tubing (UL 797). File No. E331698

## Save with the length when purchasing the 6M EMT:

- 6M (EMT) 20 feet
- Fewer fittings
- Quick and Easy installation
- Listed to UL 797 Standard and ANSI C80.3



## ELECTRICAL METALLIC TUBING – STEEL (WEIGHTS AND DIMENSIONS)

Code	Trade Size	Metric Designator	Wall Thickness	Outside Diameter	Weights of 10 Units Lengths
			mm.	mm.	kg.
C-E00050	½"	16	1.07	17.93	13.6
C-E00075	¾"	21	1.24	23.42	20.9
C-E00100	1"	27	1.45	29.54	30.4
C-E00125	1 ¼"	35	1.65	38.35	45.8
C-E00150	1 ½"	41	1.65	44.20	52.6
C-E00200	2"	53	1.65	55.80	67.1
C-E00250	2 ½"	63	1.83	73.03	98.0
C-E00300	3"	78	1.83	88.90	119.3
C-E00350	3 ½"	91	2.11	101.60	158.3
C-E00400	4"	103	2.11	114.30	178.3

NOTES: Applicable tolerances

Length: 10ft. (3.05 m) +/- ¼ in. (+/- 6.35 mm)

(1) Outside Diameter: 10.015 -/+ 2 - 2/ in. (16 - 35 +/- 0.13 mm), 2 - 10.020 -/+ 2/ in. (910.51 -/+ 103- mm). 3 +/- 0.015 in. (78 +/- 0.38 mm), 3 - 10.020 -/+ 4 - 2/ in. (910.51 -/+ 103- mm).

Colors Available:

