





[1] EU – TYPE EXAMINATION CERTIFICATE

Equipment or Protective System Intended for use in Potentially Explosive Atmospheres Directive 2014/34/EU.

[3] EU-Type Examination Certificate Number: FIDI 19 ATEX 0025 Issue:

[4] Product: Fluorescent lamp fitting

Type: **PSF 218; PSF 236; PSF 258**

PSF 218E; PSF 236E

[5] Manufacturer: TEPEx Ltd.

[6] Product: Medarska 69, 10090 Zagreb, Croatia

[7] This product and any acceptable variation thereto is specified in the schedule to this certificate and documents therein referred to.

[8] FIDITAS Ltd., Notified Body number 2829 in accordance with Article 17 of Directive 2014/34/EU of the European Parliament and of the Council, dated 26 February 2014, certifies that this product has been found to comply with the Essential Health and Safety Requirements relating to the design and construction of products intended for use in potentially explosive atmospheres given in Annex II of the Directive.

The examination and test results are recorded in confidential Report No: FIDI 19 CR 025

[9] Compliance with the Essential Health and Safety Requirements has been assured by compliance with:

EN IEC 60079-0:2018 EN 60079-1:2014 EN IEC 60079-7:2015 / A1:2018

EN 60079-18:2015 / A1:2017 EN 60079-31:2014

except in respect of those requirements listed at item 18 of the Schedule.

- [10] If the sign 'X' is placed after the certificate number, it indicates that the product is subject to Specific Conditions of Use specified in the schedule to this certificate.
- [11] This EU-Type Examination Certificate relates only to the design, examination and test of the specified product in accordance with Annex III. Further requirements of the Directive apply to the manufacturing process and supply of this products. These are not covered by this certificate.



FIDI 19 ATEX 0025



[12] The marking of the product shall include the following:

PSF 218/ PSF 236

II 2D Ex tb IIIA/IIIC T80°C Db

PSF 218E/ PSF 236E

II 2G Ex db eb mb IIC T4 Gb
II 2D Ex tb IIIC T80°C Db

II 2G Ex db eb mb IIC T4 Gb for PSF 258

II 2D Ex tb IIIA T80°C Db

FIDITAS Ltd.
Certification department

Our.ref.: 19.CRT.027 Approved:

Date: 12.11.2019. Marino Kelava, M.E.Eng.

Certificate No.:

[13] SCHEDULE

[14] EU - TYPE EXAMINATION CERTIFICATE No.: FIDI 19 ATEX 0025

[15] Description of product

Light fitting type PSF is designed in type of protection increased safety "e". The enclosure is made of fiber-reinforced polyester. The following components are built inside of enclosure: '

- interlocking switch type: PBT; type certificate FIDI 19 ATEX 0001U (I M2 Ex db eb I Mb;
 II 2G Ex db eb IIC Gb),
- lamp holders type: G13, type certificate FIDI 19 ATEX 0004U (II 2G Ex eb IIC Gb),
- electronic ballast type: SMP, type certificate FIDI 19 ATEX 0006U (II 2G Ex eb mb IIC Gb) and
- terminals type: CMC, SIRA 16 ATEX 3170U (II2G Ex eb IIC Gb).

Light fitting type PSF 218E and PSF 236E are designed to illuminate the room in case of danger and in relation to the basic type have an integrated electronic ballast type: EMEx 01/..., type certificate FIDI 19 ATEX 0005U (II2G Ex db eb mb IIC Gb).

For cable entry separately certified cable glands in type of protection increased safety 'eb' shall be used.

Technical data:	Lamp fitting type				
	PSF 218	PSF 236	PSF 258	PSF 218/E	PSF 236/E
Rated voltage [V]:	230				
Frequency [Hz]:	50				
Power [W]:	2×18	2×36	2×58	2×18	2×36
Ambient temperature [°C]:	-20 / +50 for IIIC -30 / +50 for IIC and IIIA -20 / +50 -20 / +		/ +40		
Battery:		/	/	4,8 V/6 Ah	4,8V/10Ah
Mechanical protection:	IP 66 for Tamin= -20°C IP 55 for Tamin= -30°C		IP 55	IP 66	

[16] Confidential Report No. FIDI 19 CR 025

[16.1] Routine testing

The manufacturer shall carry out routine test of dielectric strength according to clause 6.1 of the standard EN IEC 60079-7.



Certificate No.:

[17] Specific Conditions of Use

None

[18] Essential Health and Safety Requirements

Covered by the conformity with harmonized standards listed under item 9.

[19] Drawings and Documents

Title:	Drawing No.:	Rev. level:	Date:
Technical description of fluorescent light fitting		A	12.09.2019.
type PSF 218/236/258 Instructions for use of fluorescent light fitting	香	a	07.11.2019.
type PSF 218/236/258 Description of certification drawings T13.91.00.00-1 do16 Certification drawings:		ŝ.	12.09.2019.
Fluorescent light fitting PSF218	T13.91.00.00-1	:=0	12.09.2019.
	T13.91.00.00-2	3	12.09.2019.
	T13.91.00.00-3	2:	12.09.2019.
Fluorescent light fitting PSF236	T13.91.00.00-4	(4)	12.09.2019.
	T13.91.00.00-5	200	12.09.2019.
	T13.91.00.00-6	8	07.11.2019.
Fluorescent light fitting PSF258	T13.91.00.00-7	(2)	12.09.2019.
	T13.91.00.00-8		12.09.2019.
	T13.91.00.00-9	=	07.11.2019.
Fluorescent light fitting PSF218E	T13.91.00.00-10	(2)	12.09.2019.
	T13.91.00.00-11	S≅:	12.09.2019.
	T13.91.00.00-12	(**	07.11.2019
Fluorescent light fitting PSF236E	T13.91.00.00-13	V75	12.09.2019.
	T13.91.00.00-14	8 	12.09.2019.
	T13.91.00.00-15	: **	07.11.2019
Fluorescent light fitting PSF – important components	T13.91.00.00-16	18	12.09.2019.