



ZNB.CE2

(Switches)



Product	Aluminium Body Junction Boxes
Certification	SCA 20 ATEX 068X
Marking	II 2G Ex db IIB+H2 T6 Gb II 2D Ex tb IIIC T85°C Db
IP	IP 65
Ambiant Temp.	-20 °C up to +55 °C
Standarts	EN60079-0: 2018; EN60079-1: 2014; EN60079-31: 2014
Cable Entries	1/2" NPT (optional 3/4" NPT)
Body	Low Cooper Aluminium Alloy
Gaskets	NBR o-ring on Body
Paint	Electrostatic Powder Coat
Rated Voltage	220-380V
Frequency	50/60 Hz
Application	Oil refineries, Chemical and petrochemical plants, Boiler rooms etc.



ZONE 1-2 / 21-22

IP 65

$-20\text{ }^{\circ}\text{C} < T_a < +55\text{ }^{\circ}\text{C}$



ATEX Document Validation
T.C. Sanayi ve Teknoloji Bakanlığı



External Equipments				
Information		A	B	x
ZNB-CE2	0-1 Switches (Monophase 2x16A)	156	116	105
ZNB-CE2	0-1 Switches (Threephase 3x32A)	156	116	
ZNB-CE2	0-1-2 Commutator	156	116	
ZNB-CE2	1-0-2 Pole Changer	156	116	